

SHP 8-L

EHP-00080L-TU0 Hybrid Inverter

Product HIGHLIGHT



Support APP remote monitor and control and record consumption of power from solar or grid for home or small commercial users.



Highly intelligent control to limit maximum using power from grid and adjust solar or battery power to home needs based on the schedule or setting for saving grid power and electricity bills.



Highly integrated with EMS and inverter for transferring power from solar or battery to grid power for daily or any time needs.

. 6

Solar / Hybrid Inverter - TW

The series products provide hybrid inverter for home use and pure solar inverter for commercial or industrial needs.

To use green energy for solar power, the solar inverter is a critical equipment in solar power system.

Hybrid Inverter



| Series | SHP-8-L |
|-----------------------------|--|
| Model Name | EHP-00080L-TU0 |
| Input - Battery Port | |
| Max. charge/discharge power | 7.6 kW |
| Working voltage range | 380 Vdc to 450 Vdc |
| Working current | Max. 20 Adc |
| Peak efficiency | 97.4 % |
| Compatible battery | 6.9 kWh to 20.7 kWh / LFP |
| Input - PV Port | |
| Input voltage | Max. 600 Vdc |
| MPPT working voltage | 80 Vdc to 500 Vdc |
| MPPT working current | Max. 13.5 Adc (per MPPT loop) |
| Number of MPP trackers | 3 loops |
| AC Port (On-grid Mode) | |
| Wire connection | L1+L2+N+PE, split-phase |
| Grid voltage/frequency | 110/220 Vac, 60 Hz |
| Working power/current | 7.04kVA / Max. 32 A |
| AC Port (Off-grid Mode) | |
| Working voltage/frequency | 110/220 Vac, 60 Hz |
| Working power/current | 7.04 kVA / Max. 32 A |
| Interface / Communication | |
| Display | LED indicator |
| Smart control | Supported APP |
| Interface | RS485, BT+Wi-Fi (dongle) |
| General Parameter | |
| Topology | Transformer-less |
| Operating temperature | -25 °C to +60 °C (de-rated at 45 °C at rated output power) |
| Humidity | 0 % to 95 % RH, no condensation |
| Operating altitude | ≤4000 m |
| Mechnical | |
| Enclosure protection | IP65 |
| Cooling | Natural convection |
| Dimensions (W x H x D) | 500 x 628 x 178 mm |
| Weight | Approx. 24 kg |
| Installation type | Wall - mounting |
| Compliance | |
| Standards | Safety: IEC 62109-1/-2, CNS15426-1/-2 EMC: IEC61000-6-1/-3, IEC 62920 |

© 2025 Smartgreen-Solution Co., Ltd. All rights reserved. Subject to change with notice. Rev. 02 TW 2025.03



www.smartgreen-solution.com

4F,No.169,Xing'ai Rd., Neihu Dist., Taipei City 114, Taiwan, R.O.C. TEL: +886-2-2792-8558 Email: official@smartgreen-solution.com